



HOW TO ORDER

2007

Size 1/4" - 1"



Model

Available

For Example : 2007-3/4"

Features :

Reduced Port

W.P.: 1000PSI(PN63)

W.T.: -20°C ~ 250°C (-4°F ~ 482°F)

1/4" - 4"

Investment Casting Body

Blow-Out Proof Stem

Locking Device

Type of Drive: Manual

Thread End:

ANSI B1.20.1(NPT)

ISO228/1 & DIN259(G)

DIN2999 & BS21(BSPT)

Material List

No.	Component Name		Material	
1	Body	CF8M	CF8	WCB
2	Seat	PTFE/RTFE	PTFE/RTFE	PTFE/RTFE
3	Ball	SS316	SS304	SS304
4	Stem	SS316	SS304	SS304
5	Gasket	SS304	SS304	SS304
6	End Cap	SS316	SS304	SS304
7	Thrust Washer	PTFE	PTFE	SS202
8	Packing	PTFE	PTFE	SS202
9	Packing Gland	SS304	SS301	SS202
10	Handle	SS301	SS304	SS202
11	Spring Washer	SS304	SS304	PTFE
12	Hex Nut	SS304	SS301	PTFE
13	Lock	SS202	SS202	S202

Dimension List

NPS	DN	ID	L	H	W
1/4"	6	5	40	28	70
3/8"	10	7	44	28	72
1/2"	15	9.2	57	39	90
3/4"	20	12.5	60	40	95
1"	25	15	71	47	107