



### Features

- Durable Twin Hammer Impact Mechanism
- Adjustable Power Regulator
- Easy-to-service Two - Piece Construction
- Super Power And Performance Features To Tackle The Toughest Job With Ease
- Ideal For Installing/ tightening Or Removing/ loosening Threaded Fasteners And For Other Workshop Applications
- Auxiliary Handle Included
- Front Exhaust

Part No.	Description	Qty.	Part No.	Description	Qty.
1	hammer case	1	28	rear bearing	1
2	screw	4	29	rear cover gasket	1
3	spring washer	8	30	rear cover	1
4	hammer case gasket	1	31	screw	4
5	bushing	1	32	plug pin	1
6	anvil ring	1	33	reverse valve bushing	1
7	O-ring	1	34	O-ring	1
8	anvil	1	35	reverse valve	1
9	hammer frame	1	36	spring	1
10	hammer pin	2	37	steel ball	1
11	hammer	2	38	knob	1
12	hammer cage washer	1	39	screw	1
13	handle	1	40	bushing	1
14	screw	2	41	O-ring	1
15	trigger	1	42	reverse valve lever	1
16	trigger pin	1	43	valve spring	1
17	aluminium block	1	44	steel ball	1
18	limit pin	1	45	air inlet bushing	1
19	housing	1	46	throttle valve seat	1
20	front bearing	1	47	air inlet pin	1
21	front end plate	1	48	O-ring	1
22	cylinder pin	2	49	airinlet valve	1
23	cylinder	1	50	airinlet spring	1
24	rotor	1	51	O-ring	1
25	rotor blade	6	52	air inlet	1
26	end plate pin	1	53	filter	1
27	rear end plate	1			

### Specifications

MODEL	:	AT-265	AIR HOSE(ID)	:	3/8"
SQUARE DRIVE	:	3/4"	AVG. AIR CONSUMPTION	:	9.5 CFM
FREE SPEED	:	4200 RPM	WORKING. PRESSURE	:	6.3 BAR
MAX. TORQUE	:	1600 NM	LENGTH× HEIGHT	:	266×242 MM
AIR INLET	:	1/2"	WEIGHT	:	6.80 KG