



Features

- Durable Twin Hammer Impact Mechanism
- Adjustable Power Regulator
- Easy-to-service Two - Piece Construction
- Super Power And Performance Features To Tackle The Toughest Job With Ease
- Ideal For Installing/tightening Or Removing/loosening Threaded Fasteners And For Other Workshop Applications
- Auxiliary Handle Included
- Handle Exhaust

Part No.	Description	Qty.	Part No.	Description	Qty.
1	hammer case assembly	1	21	rear bearing	1
2	screw	8	22	housing	1
3	spring washer	8	23	trigger	1
4	hammer case gasket	1	24	elastic cylindrical pin	1
5	bushing	1	25	throttle valve seat	1
5	retainer ring	1	26	valve stem	1
7	o-ring	1	27	spring	1
8	anvil	1	28	exhaust board	1
9	hammer pin	1	29	filter	1
10	hammer	2	30	air inlet	1
11	hammer frame	1	31	reverse valve bushing	1
12	rear washer	1	32	reverse valve	1
13	front bearing	1	33	o-ring	1
14	front end plate	1	34	knob	1
15	elastic cylindrical pin	2	35	elastic cylindrical pin	1
16	cylinder	1	36	steel ball	1
17	rotor	1	37	spring	1
18	rotor blade	5	38	back cover gasket	1
19	rear end plate	1	39	back cover	1
20	elastic cylindrical pin	1			

Specifications

MODEL	:	AT-272	AIR HOSE(ID)	:	3/8"
SQUARE DRIVE	:	3/4"	AVG. AIR CONSUMPTION	:	9.5 CFM
FREE SPEED	:	5000 RPM	WORKING. PRESSURE	:	6.3 BAR
MAX. TORQUE	:	1300 NM	LENGTH× HEIGHT	:	242×235 MM
AIR INLET	:	3/8"	WEIGHT	:	2.60 KG