




Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

MODEL	ØD	G	L1	L2	L3	ØD1	↗
GPT04-G01	4	G1/8	5.5	24.3	38	11.5	14
GPT04-G02	4	G1/4	7.5	26.8	38	11.5	17
GPT04-G03	4	G3/8	7.5	27.3	38	1.5	20
GPT06-G01	6	G1/8	5.5	24.2	39	13.5	14
GPT06-G02	6	G1/4	7.5	26.7	39	13.5	17
GPT06-G03	6	G3/8	7.5	27.2	39	13.5	20
GPT06-G04	6	G1/2	10	29.7	39	13.5	24
GPT08-G01	8	G1/8	5.5	27	45	15	14
GPT08-G02	8	G1/4	7.5	29.5	45	15	17
GPT08-G03	8	G3/8	7.5	30	45	15	20
GPT08-G04	8	G1/2	10	32.5	45	15	24
GPT10-G01	10	G1/8	5.5	32.3	57	19	17
GPT10-G02	10	G1/4	7.5	34.8	57	19	17
GPT10-G03	10	G3/8	7.5	34.8	57	19	20
GPT10-G04	10	G1/2	10	38.3	57	19	24
GPT12-G01	12	G1/8	5.5	33.5	59	21.5	21
GPT12-G02	12	G1/4	7.5	36	59	21.5	21
GPT12-G03	12	G3/8	7.5	36	59	21.5	21
GPT12-G04	12	G1/2	10	39	59	21.5	24
GPT14-G03	14	G3/8	7.5	39.5	54	23.5	22
GPT14-G04	14	G1/2	10	43	54	23.5	24
GPT16-G03	16	G3/8	7.5	42.5	66	26.5	24
GPT16-G04	16	G1/2	10	44.5	66	26.5	24

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.8Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg (10 Torr)
Working Temperature	32~140°F	0~60°C