



## Features

- One-touch tube fittings are used in pneumatic piping.
- The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- Even after installation, the direction of the tube can be changed freely.
- Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- All R and NPT threads are pre-coated sealant.

## Specifications

MODEL	ØD	R	L1	L2	O	↻
PCF04-M5	4	M5	5.5	21	10	10
PCF04-M6	4	M6	6	21.5	10	10
PCF04-01	4	Rc1/8	8.5	24	10	14
PCF04-02	4	Rc1/4	11	26.5	10	17
PCF06-M5	6	M5	5.5	21.5	12	12
PCF06-M6	6	M6	6	22	12	12
PCF06-01	6	Rc1/8	8.5	24.5	12	14
PCF06-02	6	Rc1/4	11	27	12	17
PCF06-03	6	Rc3/8	12	28	12	21
PCF06-04	6	Rc1/2	14	30	12	24
PCF08-01	8	Rc1/8	8.5	26	14	14
PCF08-02	8	Rc1/4	11	28.5	14	17
PCF08-03	8	Rc3/8	12	29.5	14	21
PCF08-04	8	Rc1/2	14	31.5	14	24
PCF10-01	10	Rc1/8	8.5	29.5	17	17
PCF10-02	10	Rc1/4	11	32.7	17	17
PCF10-03	10	Rc3/8	12	33	17	21
PCF10-04	10	Rc1/2	14	35.7	17	24
PCF12-01	12	Rc1/8	8.5	31	20	21
PCF12-02	12	Rc1/4	11	33.5	20	21
PCF12-03	12	Rc3/8	12	34.5	20	21
PCF12-04	12	Rc1/2	14	36.5	20	24
PCF16-03	16	Rc3/8	12	36.5	24	24
PCF16-04	16	Rc1/2	14	38.5	24	24

### Fluid Type

**Air (No other type of gas or liquid)**

Working Pressure Range

0~150PSI

0~9.9Kgf/cm<sup>2</sup> (0~990KPa)

Negative Pressure

-29.5 in Hg

-750mm Hg (10 Torr)

Working Temperature

32~140°F

0~60°C